





Price List (PLC, HMI, SCADA) for Vietnam





Updated Jun. 4, 2018

LSIS Co., Ltd.

LSIS Co., Ltd.					Giá
Series	Part number		Description		
XGB	Main unit for XBM (Connector type) (Ladder language)		XBM-DN16S	DC24 power supply, 8 DC24V input, 8 TR(NPN : Sink) output, Built-in Positioning Function	5.070.000
			XBM-DR16S	DC24 power supply, 8 DC24V input, 8 Relay output, Built-in Positioning Function	5.070.000
			XBM-DN32S	DC24 power supply, 16 DC24V input, 16 TR(NPN : Sink) output, Built-in Positioning Function	6.460.000
			XBM-DN32H	DC24 power supply, 16 DC24V input, 16 TR(NPN : Sink) output, Built-in Positioning Function	7.200.000
	Main unit for XBC (Terminal block type) (Ladder language)		XBC-DR32H	AC110/240V power supply, 16 DC24 input, 16 Relay output, Built-in Positioning Function	9.930.000
			XBC-DN32H	AC110/240V power supply, 16 DC24 input, 16 TR(NPN : Sink) output, Built-in Positioning Function	9.930.000
			XBC-DR64H	AC110/240V power supply, 32 DC24 input, 32 Relay output, Built-in Positioning Function	12.410.000
			XBC-DN64H	AC110/240V power supply, 32 DC24 input, 32 TR(NPN : Sink) output, Built-in Positioning Function	12.410.000
			XBC-DR32H/DC	DC24V power supply, 16 DC24 input, 16 Realy output, Built-in Positioning Function	9.930.000
			XBC-DN32H/DC	DC24V power supply, 16 DC24 input, 16 TR(NPN : Sink) output, Built-in Positioning Function	9.930.000
			XBC-DR64H/DC	DC24V power supply, 32 DC24 input, 32 Realy output, Built-in Positioning Function	12.410.000
			XBC-DN64H/DC	DC24V power supply, 32 DC24 input, 32 TR(NPN : Sink) output, Built-in Positioning Function	12.410.000
	Main unit for XEC (Terminal Block type) (IEC language)		XEC-DR32H	AC110/240V power supply, 16 DC24 input, 16 Relay output, Built-in Positioning Function	9.930.000
			XEC-DN32H	AC110/240V power supply, 16 DC24 input, 16 TR(NPN : Sink) output, Built-in Positioning Function	9.930.000
			XEC-DR64H	AC110/240V power supply, 32 DC24 input, 32 Relay output, Built-in Positioning Function	12.410.000
			XEC-DN64H	AC110/240V power supply, 32 DC24 input, 32 TR(NPN : Sink) output, Built-in Positioning Function	12.410.000
			XEC-DP32H	AC110/240V power supply, 16 DC24 input, 16 TR(PNP : Sink) output, Built-in Positioning Function	9.930.000
			XEC-DP64H	AC110/240V power supply, 32 DC24 input, 32 TR(PNP : Sink) output, Built-in Positioning Function	12.410.000
			XEC-DR32H/D1	DC12~24V power supply, 16 DC24 input, 16 Relay	9.930.000
			XEC-DR64H/D1	DC12~24V power supply, 32 DC24 input, 32 Relay	12.410.000
			XBC-DR10E	AC110/240V power supply, 6 DC24 input, 4 Relay output	2.980.000
			XBC-DN10E	AC110/240V power supply, 6 DC24 input, 4 Tr. (NPN) output	2.980.000
			XBC-DP10E	AC110/240V power supply, 6 DC24 input, 4 Tr. (PNP) output	2.980.000

Main unit for XBC (Economic type)		XBC-DR14E	AC110/240V power supply, 8 DC24 input, 6 Relay output	3.230.000
		XBC-DN14E	AC110/240V power supply, 8 DC24 input, 6 Tr. (NPN) output	3.230.000
		XBC-DP14E	AC110/240V power supply, 8 DC24 input, 6 Tr. (PNP) output	3.230.000
		XBC-DR20E	AC110/240V power supply, 12 DC24 input, 8 Relay output	3.670.000
		XBC-DN20E	AC110/240V power supply, 12 DC24 input, 8 Tr. (NPN) output	3.670.000
		XBC-DP20E	AC110/240V power supply, 12 DC24 input, 8 Tr. (PNP) output	3.670.000
		XBC-DR30E	AC110/240V power supply, 18 DC24 input, 12 Relay output	3.920.000
		XBC-DN30E	AC110/240V power supply, 18 DC24 input, 12 Tr. (NPN) output	3.920.000
		XBC-DP30E	AC110/240V power supply, 18 DC24 input, 12 Tr. (PNP) output	3.920.000
Main unit for IEC (Economic type)		XEC-DR10E	AC110/240V power supply, 6 DC24 input, 4 Relay output	2.980.000
		XEC-DN10E	AC110/240V power supply, 6 DC24 input, 4 Tr. (NPN) output	2.980.000
		XEC-DP10E	AC110/240V power supply, 6 DC24 input, 4 Tr. (PNP) output	2.980.000
		XEC-DR14E	AC110/240V power supply, 8 DC24 input, 6 Relay output	3.230.000
		XEC-DN14E	AC110/240V power supply, 8 DC24 input, 6 Tr. (NPN) output	3.230.000
		XEC-DP14E	AC110/240V power supply, 8 DC24 input, 6 Tr. (PNP) output	3.230.000
		XEC-DR20E	AC110/240V power supply, 12 DC24 input, 8 Relay output	3.670.000
		XEC-DN20E	AC110/240V power supply, 12 DC24 input, 8 Tr. (NPN) output	3.670.000
		XEC-DP20E	AC110/240V power supply, 12 DC24 input, 8 Tr. (PNP) output	3.670.000
		XEC-DR30E	AC110/240V power supply, 18 DC24 input, 12 Relay output	3.920.000
		XEC-DN30E	AC110/240V power supply, 18 DC24 input, 12 Tr. (NPN) output	3.920.000
		XEC-DP30E	AC110/240V power supply, 18 DC24 input, 12 Tr. (PNP) output	3.920.000
		XBC-DN20SU	AC110/240V power supply, 12 DC24 input, 8 Tr.output (NPN)	5.660.000
		XBC-DR20SU	AC110/240V power supply, 12 DC24 input, 8 Relay output	5.660.000
		XBC-DP20SU	AC110/240V power supply, 12 DC24 input, 8 Tr.output (PNP)	5.660.000
		XBC-DN30SU	AC110/240V power supply, 18 DC24 input, 12Tr.output(NPN)	6.160.000
		XBC-DR30SU	AC110/240V power supply, 18 DC24 input, 12 Relay output	6.160.000




		XBC-DP30SU	AC110/240V power supply, 18 DC24 input, 12Tr.output(PNP)	6.160.000
		XBC-DN40SU	AC110/240V power supply, 24 DC24 input, 16Tr.output(NPN)	7.200.000
		XBC-DR40SU	AC110/240V power supply, 24 DC24 input, 16 Relay output	7.400.000
Standard type (IEC)		XBC-DP40SU	AC110/240V power supply, 24 DC24 input, 16Tr.output(PNP)	7.200.000
		XBC-DN60SU	AC110/240V power supply, 32 DC24 input, 28Tr.output(NPN)	8.690.000
		XBC-DR60SU	AC110/240V power supply, 32 DC24 input, 28 Relay output	8.890.000
		XBC-DP60SU	AC110/240V power supply, 32 DC24 input, 28Tr.output(PNP)	8.690.000
		XEC-DN20SU	AC110/240V power supply, 12 DC24 input, 8 Tr.output(NPN)	5.660.000
		XEC-DR20SU	AC110/240V power supply, 12 DC24 input, 8 Relay output	5.660.000
		XEC-DP20SU	AC110/240V power supply, 12 DC24 input, 8 Tr.output(PNP)	5.660.000
		XEC-DN30SU	AC110/240V power supply, 18 DC24 input, 12Tr.output(NPN)	6.160.000
		XEC-DR30SU	AC110/240V power supply, 18 DC24 input, 12 Relay output	6.160.000
		XEC-DP30SU	AC110/240V power supply, 18 DC24 input, 12Tr.output(PNP)	6.160.000
		XEC-DN40SU	AC110/240V power supply, 24 DC24 input, 16Tr.output(NPN)	7.200.000
		XEC-DR40SU	AC110/240V power supply, 24 DC24 input, 16 Relay output	7.400.000
XBC U (AC)		XEC-DP40SU	AC110/240V power supply, 24 DC24 input, 16Tr.output(PNP)	7.200.000
		XEC-DN60SU	AC110/240V power supply, 32 DC24 input, 28 Tr.output(NPN)	8.690.000
		XEC-DR60SU	AC110/240V power supply, 32 DC24 input, 28 Relay output	8.890.000
		XEC-DP60SU	AC110/240V power supply, 32 DC24 input, 28Tr.output(PNP)	8.690.000
		XBC-DN32U	AC110/240V power supply, 16 DC24 input, 16 TR(NPN : Sink) output	10.920.000
		XBC-DN32UA	AC110/240V power supply, 16 DC24 input, 16 TR(NPN : Sink) output, Built-in Analog	17.380.000
		XBC-DN32UP	AC110/240V power supply, 16 DC24 input, 16 TR(NPN : Sink) output, Built-in Positioning Function	14.900.000
		XBC-DP32U	AC110/240V power supply, 16 DC24 input, 16 TR(PNP : Source) output	10.920.000
		XBC-DP32UA	AC110/240V power supply, 16 DC24 input, 16 TR((PNP : Source) output, Built-in Analog	17.380.000
		XBC-DP32UP	AC110/240V power supply, 16 DC24 input, 16 TR((PNP : Source) output, Built-in Positioning Function	14.900.000
		XBC-DR28U	AC110/240V power supply, 16 DC24 input, 12 Relay output output	10.920.000

		XBC-DR28UA	AC110/240V power supply, 16 DC24 input, 12 Relay output, Built-in Analog	17,380.000
		XBC-DR28UP	AC110/240V power supply, 16 DC24 input, 12 Relay output, Built-in Positioning Function	14,900.000
XBC U (DC)		XBC-DN32U/DC	DC24V power supply, 16 DC24 input, 16 TR(NPN : Sink) output	10,920.000
		XBC-DN32UA/DC	DC24V power supply, 16 DC24 input, 16 TR(NPN : Sink) output, Built-in Analog	17,380.000
		XBC-DN32UP/DC	DC24V power supply, 16 DC24 input, 16 TR(NPN : Sink) output, Built-in Positioning Function	14,900.000
		XBC-DP32U/DC	DC24V power supply, 16 DC24 input, 16 TR(PNP : Source) output	10,920.000
		XBC-DP32UA/DC	DC24V power supply, 16 DC24 input, 16 TR((PNP : Source) output, Built-in Analog	17,380.000
		XBC-DP32UP/DC	DC24V power supply, 16 DC24 input, 16 TR((PNP : Source) output, Built-in Positioning Function	14,900.000
		XBC-DR28U/DC	DC24V power supply, 16 DC24 input, 12 Relay output output	10,920.000
		XBC-DR28UA/DC	DC24V power supply, 16 DC24 input, 12 Relay output, Built-in Analog	17,380.000
		XBC-DR28UP/DC	DC24V power supply, 16 DC24 input, 12 Relay output, Built-in Positioning Function	14,900.000
XEC U (AC)		XEC-DN32U	AC110/240V power supply, 16 DC24 input, 16 TR(NPN : Sink) output	10,920.000
		XEC-DN32UA	AC110/240V power supply, 16 DC24 input, 16 TR(NPN : Sink) output, Built-in Analog	17,380.000
		XEC-DN32UP	AC110/240V power supply, 16 DC24 input, 16 TR(NPN : Sink) output, Built-in Positioning Function	14,900.000
		XEC-DP32U	AC110/240V power supply, 16 DC24 input, 16 TR(PNP : Source) output	10,920.000
		XEC-DP32UA	AC110/240V power supply, 16 DC24 input, 16 TR(PNP : Source) output, Built-in Analog	17,380.000
		XEC-DP32UP	AC110/240V power supply, 16 DC24 input, 16 TR(PNP : Source) output, Built-in Positioning Function	14,900.000
		XEC-DR28U	AC110/240V power supply, 16 DC24 input, 12 Relay output output	10,920.000
		XEC-DR28UA	AC110/240V power supply, 16 DC24 input, 12 Relay output, Built-in Analog	17,380.000
		XEC-DR28UP	AC110/240V power supply, 16 DC24 input, 12 Relay output, Built-in Positioning Function	14,900.000
XEC U (DC)		XEC-DN32U/DC	DC24V power supply, 16 DC24 input, 16 TR(NPN : Sink) output	10,920.000
		XEC-DN32UA/DC	DC24V power supply, 16 DC24 input, 16 TR(NPN : Sink) output, Built-in Analog	17,380.000
		XEC-DN32UP/DC	DC24V power supply, 16 DC24 input, 16 TR(NPN : Sink) output, Built-in Positioning Function	14,900.000
		XEC-DP32U/DC	DC24V power supply, 16 DC24 input, 16 TR(PNP : Source) output	10,920.000
		XEC-DP32UA/DC	DC24V power supply, 16 DC24 input, 16 TR(PNP : Source) output, Built-in Analog	17,380.000
		XEC-DP32UP/DC	DC24V power supply, 16 DC24 input, 16 TR(PNP : Source) output, Built-in Positioning Function	14,900.000


Expension I/O		XEC-DR28U/DC	DC24V power supply, 16 DC24 input, 12 Relay output output	10.920.000
		XEC-DR28UA/DC	DC24V power supply, 16 DC24 input, 12 Relay output, Built-in Analog	17.380.000
		XEC-DR28UP/DC	DC24V power supply, 16 DC24 input, 12 Relay output, Built-in Positioning Function	14.900.000
		XBE-DC08A	DC24V input 8 points	2.700.000
		XBE-DC16A	DC24V input 16 points	3.060.000
		XBE-DC16B	DC12V/DC24V input 16 points	3.370.000
		XBE-DC32A	DC24V input 32 points	3.530.000
		XBE-RY08A	Relay output 8 points	3.060.000
		XBE-RY08B	Relay output 4 points, Seperated common	3.060.000
		XBE-RY16A	Relay output 16 points	3.890.000
		XBE-DR16A	DC24V input 8 points / Relay output 8 points	3.890.000
		XBE-TN08A	Transistor(NPN : Sink) output 8 points	2.700.000
		XBE-TN16A	Transistor(NPN : Sink) output 16 points	3.060.000
		XBE-TN32A	Transistor(NPN : Sink) output 32 points	3.530.000
		XBE-TP08A	Transistor(PNP : Source) output 8 points	2.700.000
		XBE-TP16A	Transistor(PNP : Source) output 16 points	3.060.000
		XBE-TP32A	Transistor(PNP : Source) output 32 points	3.530.000
Communication		XBL-C41A	Cnet (RS-422/485) I/F	3.890.000
		XBL-C21A	Cnet (RS-232C) I/F [modem communication]	3.890.000
		XBL-EIMT	RAPiEnet - LS Protocol based Ethernet	6.700.000
		XBL-EIMF	RAPiEnet - Fiber optic	10.380.000
		XBL-EIMH	RAPiEnet - Hybrid	8.310.000
		XBL-EMTA	Ethernet I/F	5.190.000
		XBL-CMEA	CANOpen Master	7.530.000
		XBL-CSEA	CANOpen Slave	7.530.000
		XBL-PMEC	Profibus Master	10.380.000



Special





XBL-PSEA	Profibus Slave	7.530.000
XBL-RMEA	Rnet master	7.790.000
XBL-DSEA	Dnet slave	7.790.000
XBF-AD04A	4 Channel Analog input (Current/Voltage) (12BIT)	6.540.000
XBF-AD08A	8 Channel Analog input (Current/Voltage) (12BIT)	9.810.000
XBF-DC04A	4 Channel Analog output (Current) (12BIT)	6.540.000
XBF-DV04A	4 Channel Analog output (Voltage) (12BIT)	6.540.000
XBF-AH04A	2 Channel Analog input, 2 Channel Analog output	6.700.000
XBF-RD04A	4 Channel RTD (Resistance Temperature Detect) input	8.310.000
XBF-RD01A	1 Channel RTD (Resistance Temperature Detect) input	5.190.000
XBF-TC04S	4 Channel Thermocouple input	8.770.000
XBF-PD02A	Pulse (OC) output 2 axis	6.230.000
XBF-PN08B	EtherCAT standard 8 axis	12.980.000
XBF-PN04B	EtherCAT standard 4 axis	9.090.000
XBF-HO02A	HSC Open collector	6.230.000
XBF-HD02A	HSC Line drive	6.230.000
XBF-AD04C	4 Channel Analog input (Current/Voltage) (14BIT)	7.790.000
XBF-DC04C	4 Channel Analog output (Current) (14BIT)	7.790.000
XBF-DV04C	4 Channel Analog output (Voltage) (14BIT)	7.790.000
XBF-LD02S	Loacell module, 2 channels	7.270.000
XBF-TC04TT	Temperature controller. Thermocouple input	10.380.000
XBF-TC04RT	Temperature controller. RTD input	9.090.000
XBO-M2MB	Program read/write, Program back up	1.670.000
XBO-DC04A	DC input (High speed counter in XBC-xxxS)	1.100.000
XBO-TN04A	TR output (Pulse output in XBC-xxxS)	950.000
XBO-AD02A	Current/Voltage input 2Ch	1.720.000

	Option board		XBO-DA02A	Current/Voltage output 2Ch	1.720.000	
			XBO-AH02A	Current/Voltage input 1Ch / output 1Ch	1.910.000	
			XBO-RD01A	RTD 1Ch	2.050.000	
			XBO-TC02A	Thermo couple 2Ch	2.140.000	
			XBO-RTCA	Real Time Clock Pack	950.000	
Download cable			PMC-310S	Connection cable(PC to PLC), 9pin(PC)-6pin(PLC), Soft tube type cable for XBM	450.000	
			USB-301A 2.0	Connection cable(PC to PLC), USB 2.0	450.000	
BATTERY			XBC & XEC	BATT,LITHIUM,CR2032,WK13,3V,220mAh,MAXELL	510.000	
XGK & XGI	XGK CPU		XGK-CPUE	CPU Module, User Program Memory 16 Ksteps, 84ns/step, Max. 1,536 I/O, Built-in RS-232C, USB	8.440.000	
			XGK-CPUS	CPU Module, User Program Memory 32 Ksteps, 84ns/step, Max. 3,072 I/O, Built-in RS-232C, USB	12.410.000	
			XGK-CPUA	CPU Module, User Program Memory 32 Ksteps, 28ns/step, Max. 3,072 I/O, Built-in RS-232C, USB	14.900.000	
			XGK-CPUH	CPU Module, User Program Memory 64 Ksteps, 28ns/step, Max. 6,144 I/O, Built-in RS-232C, USB	17.380.000	
			XGK-CPUU	CPU Module, User Program Memory 128 Ksteps, 28ns/step, Max. 6,144 I/O, Built-in RS-232C, USB	20.360.000	
			XGK-CPUUN	CPU Module, User Program Memory 256 Ksteps, 8.5ns/step, Max. 6,144 I/O, Built-in Ethernet, USB	21.100.000	
			XGK-CPUHN	CPU Module, User Program Memory 128 Ksteps, 8.5ns/step, Max. 6,144 I/O, Built-in Ethernet, USB	21.600.000	
			XGK-CPUSN	CPU Module, User Program Memory 64 Ksteps, 8.5ns/step, Max. 3,072 I/O, Built-in Ethernet, USB	22.350.000	
	XGI CPU		XGI-CPUE	CPU Module, User Program Memory 64 Kbytes, 84ns/step, Max. 1,536 I/O, Built-in RS-232C, USB	8.440.000	
			XGI-CPUS	CPU Module, User Program Memory 128 Kbytes, 28ns/step, Max. 3,072 I/O, Built-in RS-232C, USB	11.420.000	
			XGI-CPUH	CPU Module, User Program Memory 512 Kbytes, 28ns/step, Max. 6,144 I/O, Built-in RS-232C, USB	17.380.000	
			XGI-CPUU	CPU Module, User Program Memory 1 Mbytes, 28ns/step, Max. 6,144 I/O, Built-in RS-232C, USB	20.360.000	
			XGI-CPUUN	CPU Module, User Program Memory 1 Mbytes, 28ns/step, Max. 6,144 I/O, Built-in Ethernet, USB	24.430.000	
	Power		XGP-ACF1	Power Supply Module, AC Free Voltage / DC5V 3A, DC24V 0.6A	3.810.000	
			XGP-ACF2	Power Supply Module, AC Free Voltage / DC5V 6A	3.810.000	
			XGP-AC23	Power Supply Module, AC 220V, DC5V 8A	3.670.000	
			XGP-DC42	Power Supply Module, DC24V, DC5V 6A	3.480.000	
				XGB-M04A	Base board (Main), 4 slots for I/O Module	4.930.000

Main slot		XGB-M06A	Base board (Main), 6 slots for I/O Module	5.450.000
		XGB-M08A	Base board (Main), 8 slots for I/O Module	6.230.000
		XGB-M12A	Base board (Main), 12 slots for I/O Module	7.840.000
Extansion slot		XGB-E04A	Base board (Ext.), 4 slots for I/O Module	4.930.000
		XGB-E06A	Base board (Ext.), 6 slots for I/O Module	5.450.000
		XGB-E08A	Base board (Ext.), 8 slots for I/O Module	6.230.000
		XGB-E12A	Base board (Ext.), 12 slots for I/O Module	7.840.000
Input		XGI-A12A	AC 110V Input 16 points	3.110.000
		XGI-A21A	AC 220V Input 8 points	3.110.000
		XGI-D21A	DC 24V Input 8 points (Current Source Type)	2.080.000
		XGI-D22A	DC 24V Input 16 points (Current Sink/Source Type)	2.600.000
		XGI-D22B	DC 24V Input 16 points (Current Source Type)	2.600.000
		XGI-D24A	DC 24V Input 32 points (Current Sink/Source Type)	4.670.000
		XGI-D24B	DC 24V Input 32 points (Current Source Type)	4.670.000
		XGI-D28A	DC 24V Input 64 points (Current Sink/Source Type)	6.330.000
		XGI-D28B	DC 24V Input 64 points (Current Source Type)	6.330.000
Output		XGQ-RY1A	Relay Output 8 points (AC 240V, DC24V 2A)	3.370.000
		XGQ-RY2A	Relay Output 16 points (AC 240V, DC24V 2A)	4.150.000
		XGQ-RY2B	Relay Output 16 points (AC 240V, DC24V 2A, Varistor, CR absorber)	4.150.000
		XGQ-SS2A	SSR(Current Sink Type) Output 16 points(AC 100~240V 1A)	6.230.000
		XGQ-TR2A	Tr.(NPN Type) Output 16 points(DC12/24V 0.5A)	3.630.000
		XGQ-TR2B	Tr.(PNP Type) Output 16 points(DC12/24V 0.5A)	3.630.000
		XGQ-TR4A	Tr.(NPN Type) Output 32 points(DC12/24V 0.1A)	4.670.000
		XGQ-TR4B	Tr.(PNP Type) Output 32 points(DC12/24V 0.1A)	4.670.000
		XGQ-TR8A	Tr.(NPN Type) Output 64 points(DC12/24V 0.1A)	6.330.000
		XGQ-TR8B	Tr.(PNP Type) Output 64 points(DC12/24V 0.1A)	6.330.000

Hybrid digital I/O		XGH-DT4A	DC 24V input 16 points(current source / sink input), Tr.(NPN Type) Output, 16 points (DC 12/24V 0.1A)	4.670.000
Analog Input		XGF-AV8A	Voltage input, 8 channels (14 BIT)	8.310.000
		XGF-AC8A	Current input, 8 channels (14 BIT)	8.310.000
		XGF-AD8A	Voltage/Current input, 8 channels (14 BIT)	9.860.000
		XGF-AD4S	Voltage/Current input, 4 channels, Isolation type (16 BIT)	13.500.000
		XGF-AD16A	Voltage/Current input, 16 channels (14 BIT)	12.980.000
Analog Output		XGF-DV4A	Voltage output, 4 channels (14 BIT)	8.770.000
		XGF-DC4A	Current output, 4 channels (14 BIT)	9.340.000
		XGF-DV8A	Voltage output, 8 channels (14 BIT)	10.380.000
		XGF-DC8A	Current output, 8 channels (14 BIT)	10.380.000
		XGF-DV4S	Voltage output, 4 channels, Isolation type (14 BIT)	15.570.000
		XGF-DC4S	Current output, 4 channels, Isolation type (14 BIT)	15.570.000
Hybrid analog I/O		XGF-AH6A	Current input 4 channels & Current 2 output channels	12.980.000
Hybrid analog I/O		XGF-AW4S	2 Wire, Voltage/Current input, 4 channels, Isolation type (16 BIT)	16.610.000
HSC		XGF-HO2A	Pulse (OC) input, 2 channels	7.270.000
		XGF-HD2A	Pulse (LD) input, 2 channels	7.270.000
		XGF-HO8A	Pulse (OC) input, 8 channels	10.900.000
Position		XGF-PO1H	Pulse (OC) output 1 axis (New position model with XG-PM S/W)	10.900.000
		XGF-PD1H	Pulse (LD) output 1 axis (New position model with XG-PM S/W)	10.900.000
		XGF-PO2H	Pulse (OC) output 2 axis (New position model with XG-PM S/W)	12.980.000
		XGF-PD2H	Pulse (LD) output 2 axis (New position model with XG-PM S/W)	12.980.000
		XGF-PO3H	Pulse (OC) output 3 axis (New position model with XG-PM S/W)	15.570.000
		XGF-PD3H	Pulse (LD) output 3 axis (New position model with XG-PM S/W)	15.570.000
		XGF-PO4H	Pulse (LD) output 4 axis (New position model with XG-PM S/W)	18.170.000
		XGF-PD4H	Pulse (LD) output 4 axis (New position model with XG-PM S/W)	18.170.000
		XGF-PN8B	EtherCAT standard 8 axis	20.770.000

		XGF-M32E	EtherCAT motion controller 32 axis	25.960.000
Temp.		XGF-TC4S	Temperature (TC) Input, 4 channels, Isolation type	18.170.000
		XGF-RD4S	Temperature (RTD) Input, 4 channels, Isolation type	11.780.000
		XGF-RD4A	Temperature (RTD) Input, 4 channels	8.150.000
		XGF-RD8A	Temperature (RTD) Input, 8 channels	13.810.000
Temp. Control		XGF-TC4UD	Temperature Controller, 4 loops, Universal, Insolation type	28.550.000
		XGF-TC4RT	Temperature Controller, 4 loops, RTD, Insolation type	14.020.000
Cnet		XGL-CH2B	Computer Communication RS-232C/RS-422 (Each 1ch)	8.570.000
		XGL-C22B	Computer Communication RS-232C, 2ch	8.410.000
		XGL-C42B	Computer Communication RS-422, 2ch	8.410.000
Rnet		XGL-RMEA	R-net Master, 1Mbps, TP	7.160.000
Fnet		XGL-FMEA	F-net Master	6.230.000
Dnet		XGL-DMEB	Devicenet, Master, 500Kbps, ODVA standard	23.880.000
Pnet		XGL-PMEB	Profibus-DP Master, 12Mbps, OP standard (Configuration tool : sycon); not including connector	16.090.000
		XGL-PSRA	Profibus remote module	10.380.000
		XGL-PSEA	Profibus slave module	10.380.000
Ethernet		XGL-EFMTB	Open FEnet Optical, Master, 100/10Mbps, SC type	6.490.000
		XGL-EFMFB	Open FEnet Electric, Master, 100 /10Mbps, RJ-45	9.710.000
		XGL-ESHF	FEnet Fiber Optic Switch Module, 100Mbps, SC type, 2Port(for Ring)	25.960.000
		XGL-EH5T	Ethernet Hub 5 Port UTP	3.740.000
Dedicated Ethernet		XGL-EDMF	Dedicated FEnet Optical, Master, 100/10Mbps, SC type	10.380.000
		XGL-EDMT	Dedicated FEnet Electric, Master, 100 /10Mbps, RJ-45	9.140.000
Ethernet IP		XGL-EIPT	EtherNet/IP I/F module	9.340.000
BACnet		XGL-BIPT	BACnet module	9.340.000
		XOL-EIMT	Dedicated FEnet Electric, Master, 100 /10Mbps, RJ-45, 2Port(for PC)	15.420.000

	RAPIenet		XOL-EIMF	Dedicated FEnet Optical, Master, 100/10Mbps, LC type, 2Port(for PC)	17.550.000
			XGL-EIMT	Dedicated FEnet Electric, Master, 100 /10Mbps, RJ-45, 2Port	9.340.000
			XGL-EIMF	Dedicated FEnet Optical, Master, 100/10Mbps, LC type, 2Port	11.680.000
			XGL-EIMH	Dedicated FEnet Electric, Optical, Master, 100 /10Mbps, Hybrid (RJ-45,LC type) , 2Port	10.280.000
			XGL-ES4T	Multiport RAPIenet Switch	12.980.000
	Ext. Cable		XGC-E041	Expansion Cable Length:0.4m	1.490.000
			XGC-E061	Expansion Cable Length:0.6m	1.640.000
			XGC-E121	Expansion Cable Length:1.2m	1.890.000
			XGC-E301	Expansion Cable Length:3.0m	2.480.000
			XGC-E501	Expansion Cable Length:5.0m	3.480.000
			XGC-E102	Expansion Cable Length:10m	4.470.000
			XGC-E152	Expansion Cable Length:15m	5.960.000
	Recorder		XGF-SOEA	Sequence Of Events Recorder (per 1ms)	11.680.000
	Data log		XGF-DL16A	Data log module	11.680.000
	HART		XGF-AC4H	HART Interface module	10.380.000
			XGF-DC4H	HART Interface module	14.280.000
	Ext. End		XGT-TERA	Extension base end connector	1.250.000
	Dummy		XGT-DMMA	Dummy Module	210.000
	Cable		K1C-50A	Computer - PLC Cable RS-232C	990.000
	Pnet connector		GPL-CON(M)	Pnet connector (Master)	1.250.000
	Pnet connector		GPL-CON(s)	Pnet connector (Slave)	1.250.000
	Battery		XGT CPU	BATT,LITHIUM,CR17335-CN763S,3V,2AH,MITSUBISHI	400.000
K120S GM7U	Main Unit (K120S Economic		K7M-DR10UE	AC100/240V Power supply, DC24V Input 6 points, Relay Output 4 points)	3.330.000
			K7M-DR14UE	AC100/240V Power supply, DC24V Input 8 points, Relay Output 6 points)	3.770.000
			K7M-DR20UE	AC100/240V Power supply, DC24V Input 12 points, Relay Output 8 points)	4.470.000
			K7M-DR30UE	AC100/240V Power supply, DC24V Input 18 points, Relay Output 12 points)	5.560.000

(K120S Economic type)		K7M-DR10UE/DC	DC24V Power supply, DC24V Input 6 points, Relay Output 4 points)	3.330.000
		K7M-DR14UE/DC	DC24V Power supply, DC24V Input 8 points, Relay Output 6 points)	3.770.000
		K7M-DR20UE/DC	DC24V Power supply, DC24V Input 12 points, Relay Output 8 points)	4.470.000
		K7M-DR30UE/DC	DC24V Power supply, DC24V Input 18 points, Relay Output 12 points)	5.560.000
Main Unit (K120S Standard type)		K7M-DRT20U	AC100/240V Power supply	5.960.000
		K7M-DRT30U	AC100/240V Power supply, DC24V Input 18 points, Relay Output 4 points, Transistor Ouput 8 points)	7.450.000
		K7M-DRT40U	AC100/240V Power supply, DC24V Input 24 points, Relay Output 4 points, Transistor Ouput 12 points)	8.890.000
		K7M-DRT60U	AC100/240V Power supply, DC24V Input 36 points, Relay Output 4 points, Transistor Ouput 20 points)	11.620.000
		K7M-DRT20U/DC	DC24V Power supply, DC24V Input 12 points, Relay Output 4 points, Transistor Ouput 4 points)	5.020.000
		K7M-DRT30U/DC	DC24V Power supply, DC24V Input 18 points, Relay Output 4 points, Transistor Ouput 8 points)	6.360.000
		K7M-DRT40U/DC	DC24V Power supply, DC24V Input 24 points, Relay Output 4 points, Transistor Ouput 12 points)	7.800.000
		K7M-DRT60U/DC	DC24V Power supply, DC24V Input 36 points, Relay Output 4 points, Transistor Ouput 20 points)	10.230.000
		K7M-DR20U	AC100/240V Power supply DC24V Input 12 points, Relay Output 8 points)	5.020.000
		K7M-DR30U	AC100/240V Power supply DC24V Input 18 points, Relay Output 12 points)	6.360.000
		K7M-DR40U	AC100/240V Power supply DC24V Input 24 points, Relay Output 16 points)	7.800.000
		K7M-DR60U	AC100/240V Power supply DC24V Input 36 points, Relay Output 24 points)	10.230.000
		K7M-DR20U/DC	DC24V Power supply, DC24V Input 12 points, Relay Output 8 points)	5.020.000
		K7M-DR30U/DC	DC24V Power supply, DC24V Input 18 points, Relay Output 12 points)	6.360.000
		K7M-DR40U/DC	DC24V Power supply, DC24V Input 24 points, Relay Output 16 points)	7.800.000
		K7M-DR60U/DC	DC24V Power supply, DC24V Input 36 points, Relay Output 24 points)	10.230.000
		K7M-DT20U	AC100/240V Power supply, DC24V Input 12 points, Transistor Ouput 8 points)	5.020.000
		K7M-DT30U	AC100/240V Power supply, DC24V Input 18 points, Transistor Ouput 12 points)	6.360.000
		K7M-DT40U	AC100/240V Power supply, DC24V Input 24 points, Transistor Ouput 16 points)	7.800.000
		K7M-DT60U	AC100/240V Power supply, DC24V Input 36 points, Transistor Ouput 24 points)	10.230.000
		K7M-DT20U/DC	DC24V Power supply, DC24V Input 12 points, Transistor Ouput 8 points)	5.020.000
		K7M-DT30U/DC	DC24V Power supply, DC24V Input 18 points, Transistor Ouput 12 points)	6.360.000

		K7M-DT40U/DC	DC24V Power supply, DC24V Input 24 points, Transistor Ouput 16 points)	7.800.000
		K7M-DT60U/DC	DC24V Power supply, DC24V Input 36 points, Transistor Ouput 24 points)	10.230.000
Main Unit (GM7U)		G7M-DR20U	AC100/240V Power supply DC24V Input 12 points, Relay Output 8 points)	5.020.000
		G7M-DR30U	AC100/240V Power supply DC24V Input 18 points, Relay Output 12 points)	6.360.000
		G7M-DR40U	AC100/240V Power supply DC24V Input 24 points, Relay Output 16 points)	7.800.000
		G7M-DR60U	AC100/240V Power supply DC24V Input 36 points, Relay Output 24 points)	10.230.000
		G7M-DR20U/DC	DC24V Power supply, DC24V Input 12 points, Relay Output 8 points)	5.020.000
		G7M-DR30U/DC	DC24V Power supply, DC24V Input 18 points, Relay Output 12 points)	6.360.000
		G7M-DR40U/DC	DC24V Power supply, DC24V Input 24 points, Relay Output 16 points)	7.800.000
		G7M-DR60U/DC	DC24V Power supply, DC24V Input 36 points, Relay Output 24 points)	10.230.000
		G7M-DT20U(N)	AC100/240V Power supply, DC24V Input 12 points, NPN Transistor Ouput 8 points)	5.020.000
		G7M-DT30U(N)	AC100/240V Power supply, DC24V Input 18 points, NPN Transistor Ouput 12 points)	6.360.000
		G7M-DT40U(N)	AC100/240V Power supply, DC24V Input 24 points, NPN Transistor Ouput 16 points)	7.800.000
		G7M-DT60U(N)	AC100/240V Power supply, DC24V Input 36 points, NPN Transistor Ouput 24 points)	10.230.000
		G7M-DT20U(N)/DC	DC24V Power supply, DC24V Input 12 points, NPN Transistor Ouput 8 points)	5.020.000
		G7M-DT30U(N)/DC	DC24V Power supply, DC24V Input 18 points, NPN Transistor Ouput 12 points)	6.360.000
		G7M-DT40U(N)/DC	DC24V Power supply, DC24V Input 24 points, NPN Transistor Ouput 16 points)	7.800.000
		G7M-DT60U(N)/DC	DC24V Power supply, DC24V Input 36 points, NPN Transistor Ouput 24 points)	10.230.000
		G7M-DT20U(P)	AC100/240V Power supply, DC24V Input 12 points, NPN Transistor Ouput 8 points)	5.020.000
		G7M-DT30U(P)	AC100/240V Power supply, DC24V Input 18 points, NPN Transistor Ouput 12 points)	6.360.000
		G7M-DT40U(P)	AC100/240V Power supply, DC24V Input 24 points, NPN Transistor Ouput 16 points)	7.800.000
		G7M-DT60U(P)	AC100/240V Power supply, DC24V Input 36 points, NPN Transistor Ouput 24 points)	10.230.000
		G7M-DT20U(P)/DC	DC24V Power supply, DC24V Input 12 points, PNP Transistor Ouput 8 points)	5.020.000
		G7M-DT30U(P)/DC	DC24V Power supply, DC24V Input 18 points, PNP Transistor Ouput 12 points)	6.360.000
		G7M-DT40U(P)/DC	DC24V Power supply, DC24V Input 24 points, PNP Transistor Ouput 16 points)	7.800.000
		G7M-DT60U(P)/DC	DC24V Power supply, DC24V Input 36 points, PNP Transistor Ouput 24 points)	10.230.000

		G7M-DRT20U(N)	AC100/240V Power supply	5,020,000
		G7M-DRT30U(N)	AC100/240V Power supply, DC24V Input 18 points, Relay Output 4 points, Transistor Output 8 points)	6,360,000
		G7M-DRT40U(N)	AC100/240V Power supply, DC24V Input 24 points, Relay Output 4 points, Transistor Output 12 points)	7,800,000
		G7M-DRT60U(N)	AC100/240V Power supply, DC24V Input 36 points, Relay Output 4 points, Transistor Output 20 points)	10,230,000
		G7M-DRT20U(N)/dc	DC24V Power supply, DC24V Input 12 points, Relay Output 4 points, Transistor Output 4 points)	5,020,000
		G7M-DRT30U(N)/dc	DC24V Power supply, DC24V Input 18 points, Relay Output 4 points, Transistor Output 8 points)	6,360,000
		G7M-DRT40U(N)/dc	DC24V Power supply, DC24V Input 24 points, Relay Output 4 points, Transistor Output 12 points)	7,800,000
		G7M-DRT60U(N)/dc	DC24V Power supply, DC24V Input 36 points, Relay Output 4 points, Transistor Output 20 points)	10,230,000
Digital I/O		G7E-DR08A	DC24V input 4 points, Relay output 4 points, Slim size (For K120S, GM7U Only)	1,660,000
		G7E-DR10A	DC24V input 6 points, Relay output 4 points (For K80S, K120S, GM7, GM7U)	2,020,000
		G7E-DR20A	DC24V input 12 points, Relay output 8 points (For K80S[Over Version 1.7], K120S, GM7U Only)	3,480,000
		G7E-DC08A	DC24V Input 8 Points, Slim size (For K120S, GM7U Only)	1,660,000
		G7E-RY08A	Relay Output 8 Points, Slim Size (For K120S, GM7U Only)	2,020,000
		G7E-RY16A	Expansion Module Relay Output 16 Points, (For K120S, GM7U Only)	3,840,000
		G7E-TR10A	Expansion Module Transistor Output 10 Points (For K80S[Over Version 1.7], K120S, GM7U Only)	2,020,000
Analog I/O		G7F-ADHA	Analog Input 2Ch, Analog Output 1Ch (For K80S, K120S, GM7, GM7U)	4,570,000
		G7F-ADHB	Analog Input 2Ch, Analog Output 2Ch, Slim Size (For K120S & GM7U Only)	5,610,000
		G7F-AD2A	Analog Input 4Ch (For K80S[Over Version 1.4], K120S, GM7, GM7U)	5,810,000
		G7F-AD2B	Analog Input 4Ch, Slim Size (For K120S, GM7, GM7U Only)	5,810,000
		G7F-DA2I	Analog Current Output 4Ch (For K120S, GM7U Only)	5,810,000
		G7F-DA2V	Analog Voltage Output 4Ch, Slim size (For K120S, GM7U Only)	5,810,000
		G7F-AT2A	Analog Timer (0 ~ 200) 4 points (For K80S[Over Version 1.8], K120S, GM7, GM7U Only)	5,810,000
		G7F-RD2A	Resistive Temperature Detectors (4Ch.), Slim Size (For K120S, GM7U Only)	7,530,000
Communication		G7L-CUEB	RS-232C Communication Module(Modem function available)	2,020,000
		G7L-CUEC	RS-422(485) Communication Module	2,020,000
		G7L-FUEA	Fieldbus Interface Module (Fnet)	5,190,000

K200S GM6	Communication		G7L-PBEA	Profibus-DP slave interface module(Pnet)	6,900.000
			G7L-DBEA	DeviceNet slave interface module (Dnet)	5,400.000
			G7L-RUEA	Fieldbus Interface Module (Rnet) for Remote I/O	5,190.000
		RTC	G7E-RTCA	Real Time Clock Pack	1,450.000
		Memory	G7M-M256B	Flash Memory Pack(256KBytes) For Program Backup (For K120S, GM7U Only)	950.000
	K200S CPU		K3P-07AS	CPU Module, User Program Memory 7 K steps, Max. 384 I/O, Built-in RS-232C	5,460.000
			K3P-07BS	CPU Module, User Program Memory 7 K steps, Max. 384 I/O, Built-in RS-422, PID, RTC	6,260.000
			K3P-07CS	CPU Module, User Program Memory 7 K steps, Max. 384 I/O, Built-in RS-232C, PID, RTC, HSC	6,600.000
	GM6 CPU		GM6-CPUA	CPU Module, User Program Memory 68 Kbyte, Max. 384 I/O, Built-in RS-232C	5,510.000
			GM6-CPUB	CPU Module, User Program Memory 68 Kbyte, Max. 384 I/O, Built-in RS-422, PID, RTC	5,710.000
			GM6-CPUC	CPU Module, User Program Memory 68 Kbyte, Max. 384 I/O, Built-in RS-232C, PID, RTC, HSC	6,700.000
	Power Supply		GM6-PAFA	AC Input(Free), Output: DC5V 2A, DC24V 0.3A	1,480.000
			GM6-PAFB	AC Input(Free), Output: DC5V 2A, DC15V 0.5A, DC-15 0.3A (When using analog module)	1,670.000
			GM6-PAFC	AC Input(Free), Output: DC5V 3.5A, DC24V 0.3A (For 12 slot base board)	2,050.000
			GM6-PA2A	AC 220V Only, Output: DC 5V 6A	2,190.000
			GM6-PDFB	DC 12/24V Input, Output: DC 5V 2A	3,100.000
			GM6-PDFA	DC 12/24V Input, Output: DC 5V 3A, DC 15V 0.5A, DC-15V 0.2A (When using analog module)	2,480.000
	Base Board		GM6-B04M	4 slots base board (Not expandable)	1,510.000
			GM6-B06M	6 slots base board (Not expandable)	1,610.000
			GM6-B08M	8 slots base board (Not expandable)	1,770.000
			GM6-B12M	12 slots base board, Comm I/F module installation: Slot 0~7 (Not expandable)	1,870.000
	DC Input module		G6I-D21A	DC12/24V Input 8 points(Current Sink/Source Type)	1,970.000
			G6I-D22A	DC12/24V Input 16 points(Current Sink/Source Type)	2,230.000
			G6I-D22B	DC12/24V Input 16 points(Current Source Type)	2,230.000
			G6I-D24A	DC12/24V Input 32 points(Current Sink/Source Type)	4,150.000
			G6I-D24B	DC12/24V Input 32 points(Current Source Type)	4,150.000

AC Inuput module		G6I-A11A	AC110V Input 8 points	2,540.000
		G6I-A21A	AC220V Input 8 points	2,540.000
Relay output module		G6Q-RY1A	Relay Output 8 points(DC 12/24V, AC220 2A)	2,390.000
		G6Q-RY2A	Relay Output 16 points(DC 12/24V, AC220 2A)	2,800.000
		G6Q-RY2B	Relay Output 16 points(DC 12/24V, AC220 2A), Surge killer included	2,800.000
Transistor output module		G6Q-TR2A	Tr.(NPN Type) Output 16 points(DC12/24V 0.5A)	2,600.000
		G6Q-TR2B	Tr.(PNP Type) Output 16 points(DC12/24V 0.5A)	2,600.000
		G6Q-TR4A	Tr.(NPN Type) Output 32 points(DC12/24V 0.1A)	3,840.000
		G6Q-TR4B	Tr.(PNP Type) Output 32 points(DC12/24V 0.1A)	3,840.000
Triac output module		G6Q-SS1A	SSR(Current Sink Type) Output 8 points(AC 100~240V 1A)	3,110.000
I/O hybrid module		G6H-DR2A	Transistor Input 8 points / Relay Output 8 points	2,600.000
Analog I/O Module		G6F-AD2A	Analog Input 4 Channels, DC1~5V, DC0~10V, DC-10~+10V, DC4~20mA	7,010.000
		G6F-DA2V	Analog Output 4 Channels, DC-10~+10V	7,320.000
		G6F-DA2I	Analog Output 4 Channels, DC4~20mA	7,320.000
Thermocouple		G6F-TC2A	Thermocouple Input, 4 Channels(Type : K, J, E, T, B, R, S)	9,600.000
HSC module		G6F-HO1C	HSC Module, 2 Channel, 200kpps (Range : -2,147,483,648~2,147,483,648)	10,950.000
		G6F-HD1C	HSC Module, 2 Channel, 500kpps (Range : -2,147,483,648~2,147,483,648)	10,950.000
Positioning module		G6F-PP1O	Position Module, 1 axis, Pulse Output, Max. 200Kpps (Open Collector Type)	12,670.000
		G6F-PP2O	Position Module, 2 axis, Pulse Output, Max. 200Kpps (Open Collector Type)	14,590.000
		G6F-PP3O	Position Module, 3 axis, Pulse Output, Max. 200Kpps (Open Collector Type)	15,520.000
		G6F-PP1D	Position Module, 1 axis, Pulse Output, Max. 500Kpps (Line Drive Type)	12,670.000
		G6F-PP2D	Position Module, 2 axis, Pulse Output, Max. 500Kpps (Line Drive Type)	14,590.000
		G6F-PP3D	Position Module, 3 axis, Pulse Output, Max. 500Kpps (Line Drive Type)	15,520.000
		G6L-FUEA	Fieldbus(F-net) Master Module, 1Mbps(Mounted on I/O slot)	6,280.000
		G6L-RBEA	Fieldbus(F-net) Slave Module, 1Mbps(Mounted on CPU slot)	8,360.000
		G6L-DUEA	Device-net Module	11,730.000

Smart I/O	Communication Module		G6L-RUEA	Fieldbus(R-net) Master Module, 1Mbps(Mounted on I/O slot)	6.590.000
			G6L-PUEA	Profibus-DP Master Module, (1kbyte Memory)	28.550.000
			G6L-PUEB	Profibus-DP Master Module, (7kbyte Memory)	33.750.000
			G6L-CUEB	Computer Communication(RS-232C 1 channel)	5.970.000
			G6L-CUEC	Computer Communication(RS-422 1 channel)	5.970.000
			G6L-EUTB	Ethernet Module 10/100 BASE-Tx, UTP (Open Type)	14.950.000
			G6L-EUFB	Ethernet Module 100 BASE-Fx, Fiber Optic (Open Type)	16.150.000
	Dummy Module		GM6-DMMA	Dummy Module for Empty I/O Slots	160.000
	Battery		GM/MK	BATT,LITHIUM,XL-050FCW/SB-AA02(Con),3.6V,1200mAh	450.000
	Modbus		GSL-TR4C1	32 Tr.(Sink) Output, 0.1A, Modbus(RS-422/485), Fixed terminal block	5.140.000
			GSL-TR2C1	16 Tr.(Sink) Output, 0.1A, Modbus(RS-422/485), Fixed terminal block	4.410.000
			GSL-RY2C	16 Ry. Output, Modbus(RS-422/485), Fixed terminal block	4.620.000
			GSL-DT4C1	16 DC Input(Sink/Source) / 16 Tr. Output(Sink), 0.1A, Modbus(RS-422/485), Fixed terminal block	5.140.000
			GSL-D24C	32 DC Input(Sink/Source), Modbus(RS-422/485), Fixed terminal block	5.140.000
			GSL-D22C	16 DC Input(Sink/Source), Modbus(RS-422/485), Fixed terminal block	4.050.000
	Rnet		GRL-TR4C	32 Tr.(Source) Output, 0.5A, Rnet, Removable terminal block	4.670.000
			GRL-TR4C1	32 Tr.(Sink) Output, 0.5A, Rnet, Removable terminal block	4.670.000
			GRL-TR2C	16 Tr.(Source) Output, 0.5A, Rnet, Removable terminal block	3.890.000
			GRL-TR2C1	16 Tr.(Sink) Output, 0.5A, Rnet, Removable terminal block	3.890.000
			GRL-RY2C	16 Ry. Output, Rnet, Removable terminal block	4.670.000
			GRL-RY2C-G3		5.190.000
			GRL-DT4C	16 DC Input(Sink/Source) / 16 Tr. Output(Sink), 0.5A, Rnet, Removable terminal block	4.360.000
			GRL-DT4C1	16 DC Input(Sink/Source) / 16 Tr. Output(Sink), 0.5A, Rnet, Removable terminal block	4.360.000
			GRL-D22C	16 DC Input(Sink/Source), Rnet, Removable terminal block	3.630.000
			GRL-D24C	32 DC Input(Sink/Source), Rnet, Removable terminal block	4.360.000
			GRL-D24C-G3	32 DC Input(Sink/Source), Rnet, Removable terminal block	4.880.000

Profibus DP		GPL-TR4C1	32 Tr.(Sink) Output, 0.5A, Profibus-DP, Removable terminal block	5.190.000
		GPL-TR4C	32 Tr.(Source) Output, 0.5A, Profibus-DP, Removable terminal block	5.190.000
		GPL-TR2C1	16 Tr.(Sink) Output, 0.5A, Profibus-DP, Removable terminal block	4.260.000
		GPL-TR2C	16 Tr.(Source) Output, 0.5A, Profibus-DP, Removable terminal block	4.260.000
		GPL-RY2C	16 Ry. Output, Profibus-DP, Removable terminal block	5.140.000
		GPL-DT4C1	16 DC Input(Sink/Source) / 16 Tr. Output(Sink), 0.5A, Profibus-DP, Removable terminal block	5.190.000
		GPL-DT4C	16 DC Input(Sink/Source) / 16 Tr. Output(Source), 0.5A, Profibus-DP, Removable terminal block	5.190.000
		GPL-D24C	32 DC Input(Sink/Source), Profibus-DP, Removable terminal block	5.190.000
		GPL-D22C	16 DC Input(Sink/Source), Profibus-DP, Removable terminal block	4.620.000
		GPL-DV4C	Analog Voltage output, 4 channels, Profibus-DP, Removable terminal block	12.980.000
		GPL-DC4C	Analog Current output, 4 channels, Profibus-DP, Removable terminal block	12.980.000
		GPL-AV8C	Analog Voltage input, 8 channels, Profibus-DP, Removable terminal block	14.020.000
		GPL-AC8C	Analog Current input, 8 channels, Profibus-DP, Removable terminal block	14.020.000
DeviceNet		GDL-TR4C1	32 Tr.(Sink) Output, 0.5A, DeviceNet, Removable terminal block	5.450.000
		GDL-TR4C	32 Tr.(Source) Output, 0.5A, DeviceNet, Removable terminal block	5.450.000
		GDL-TR2C1	16 Tr.(Sink) Output, 0.5A, DeviceNet, Removable terminal block	4.150.000
		GDL-TR2C	16 Tr.(Source) Output, 0.5A, DeviceNet, Removable terminal block	4.150.000
		GDL-RY2C	16 Ry. Output, DeviceNet, Removable terminal block	4.930.000
		GDL-DT4C1	16 DC Input(Sink/Source) / 16 Tr. Output(Sink), 0.5A, DeviceNet, Removable terminal block	5.450.000
		GDL-DT4C	16 DC Input(Sink/Source) / 16 Tr. Output(Sourc), 0.5A, DeviceNet, Removable terminal block	5.450.000
		GDL-D24C	32 DC Input(Sink/Source), DeviceNet, Removable terminal block	5.450.000
		GDL-D22C	16 DC Input(Sink/Source), DeviceNet, Removable terminal block	4.150.000
RAPIDnet		GEL-D24C	32 DC Input(Sink/Source), RAPIDnet, Removable terminal block	6.230.000
		GEL-DT4C1	16 DC Input(Sink/Source) / 16 Tr. Output(Sourc), 0.5A, RAPIDnet, Removable terminal block	6.230.000
		GEL-TR4C1	32 Tr.(Sink) Output, 0.5A, RAPIDnet, Removable terminal block	6.230.000
		GEL-RY2C	16 Ry. Output, RAPIDnet, Removable terminal block	6.750.000

			GEL-AV8C	Analog Voltage input, 8 channels, RAPIEnet, Removable terminal block	9.340.000
			GEL-AC8C	Analog Current input, 8 channels, RAPIEnet, Removable terminal block	9.340.000
			GEL-DV4C	Analog Voltage output, 4 channels, RAPIEnet, Removable terminal block	10.380.000
			GEL-DC4C	Analog Current output, 4 channels, RAPIEnet, Removable terminal block	10.380.000
	Profibus DP		XPL-BSSA	Profibus DP adapter	6.490.000
	DeviceNet		XDL-BSSA	DeviceNet adapter	6.490.000
	Modbus TCP		XEL-BSSA	Modbus TCP adapter	7.530.000
	Ethernet I/P		XEL-BSSB	Ethernet IP adapter	7.530.000
	Rnet		XRL-BSSA	Rnet adapter	6.230.000
	XGR (Redundancy; IEC language)				0
XGR	XGR CPU		XGR-CPUH/F	CPU Module, User Program Memory 1Mbyte, Max. 131,072 I/O, Built-in RS-233C, USB, optical/optical connector supported	45.040.000
			XGR-CPUH/T	CPU Module, User Program Memory 1Mbyte, Max. 131,072 I/O, Built-in RS-232C, USB, electrical/electrical connector supported	39.880.000
			XGR-CPUH/S	Single mode CPU	47.670.000
	Power		XGR-AC12	Power Supply Module, AC 110V, DC5V 5.5A	4.290.000
			XGR-AC22	Power Supply Module, AC 220V, DC5V 5.5A	4.290.000
			XGR-AC23	Power Supply Module, AC 220V, DC5V 8.5A	5.530.000
			XGR-AC13	Power Supply Module, AC 110V, DC5V 8.5A	5.530.000
			XGR-DC42	Power Supply Module, DC 24V, DC5V 5.5A	5.530.000
	Ext. Drive		XGR-DBSH	Extension Drive Module, Connector for extension base connection(optical-electrical), Built-in USB	14.900.000
			XGR-DBSF	Extension Drive Module, Connector for extension base connection(Optical-optical), Built-in USB	14.900.000
			XGR-DBST	Extension Drive Module, Connector for extension base connection(electrical-electrical), Built-in USB	13.600.000
			XGR-DBSFS	Single mode Extension drive (Optical-optical)	18.950.000
			XGR-DBSHS	Single mode Extension drive (electrical-electrical)	18.950.000
	Ext. Drive for dual ring		XGR-DBDH	Extension Drive Module, Connector for extension base connection(optical-electrical), Built-in USB	18.950.000
			XGR-DBDF	Extension Drive Module, Connector for extension base connection(Optical-optical), Built-in USB	18.950.000
			XGR-DBDT	Extension Drive Module, Connector for extension base connection(electrical-electrical), Built-in USB	18.690.000

		Base	XGR-M06P	Base board (Main), 6 slots for I/O Module	9,760.000
			XGR-M02P	Base board (Main), 2 slots for I/O Module	8,100.000
			XGR-E12P	Base board (Ext.), 12 slots for I/O Module	10,490.000
			XGR-E08P	Base board (Ext.), 8 slots for I/O Module	8,980.000
			XGR-E12H	Base board (Ext.) for dual ring	11,580.000
		Sync. Cable	XGC-F201	LC type optical cable (multi core), length: 2 m	1,590.000
			XGC-F501	LC type optical cable (multi core), length: 5 m	2,140.000
		Dummy Module	XGR-DMMA	Dummy Module	360.000
	Smart Link	Terminal board	XTB-40H (TG7-1H40S)		500.000
		Relay (NPN)	R32C-NS5A-40P		5,460.000
		Relay (PNP)	R32C-PS5A-40P		5,460.000
			C37HD-05PB-LGP		550.000
			C37HD-10PB-LGP		650.000
			C37HD-15PB-LGP		740.000
			C37HD-20PB-LGP		890.000
			C37HD-30PB-LGP		1,040.000
			C40HF-05PB-XGP1		550.000
			C40HF-10PB-XGP1		650.000
			C40HF-15PB-XGP1		740.000
			C40HF-20PB-XGP1		890.000
			C40HF-30PB-XGP1		1,040.000
			C40HF-05PB-LGP3		550.000
			C40HF-10PB-LGP3		650.000
			C40HF-15PB-LGP3		740.000
			C40HF-20PB-LGP3		890.000
			C40HF-30PB-LGP3		1,040.000

Cable

C37HD-05PB-LG		550.000
C37HD-10PB-LG		650.000
C37HD-15PB-LG		740.000
C37HD-20PB-LG		890.000
C37HD-30PB-LG		1.040.000
C40HF-05PB-1		550.000
C40HF-10PB-1		650.000
C40HF-15PB-1		740.000
C40HF-20PB-1		890.000
C40HF-30PB-1		1.040.000
C40HF-05PB-LG3		550.000
C40HF-10PB-LG3		650.000
C40HF-15PB-LG3		740.000
C40HF-20PB-LG3		890.000
C40HF-30PB-LG3		1.040.000
C40HF-05PB-LG3		550.000
C40HF-10PB-LG3		650.000
C40HF-15PB-LG3		740.000
C40HF-20PB-LG3		890.000
C40HF-30PB-LG3		1.040.000
C40HF-05PB-LG1A		550.000
C40HF-10PB-LG1A		650.000
C40HF-15PB-LG1A		740.000
C40HF-20PB-LG1A		890.000
C40HF-30PB-LG1A		1.040.000
C40HH-05SB-XBE		550.000

C40HH-10SB-XBE		650.000
C40HH-15SB-XBE		740.000
C40HH-20SB-XBE		890.000
C40HH-30SB-XBE		1.040.000
C37HD-05PB		550.000
C37HD-10PB		650.000
C37HD-15PB		740.000
C37HD-20PB		890.000
C37HD-30PB		1.040.000
C40HF-05PB-1B		550.000
C40HF-10PB-1B		650.000
C40HF-15PB-1B		740.000
C40HF-20PB-1B		890.000
C40HF-30PB-1B		1.040.000
C40HF-05PB-3		550.000
C40HF-10PB-3		650.000
C40HF-15PB-3		740.000
C40HF-20PB-3		890.000
C40HF-30PB-3		1.040.000
R40H/20HH-05S-XBM3		550.000
R40H/20HH-10S-XBM3		650.000
C40HH-05SB-XBI		550.000
C40HH-10SB-XBI		650.000
C40HH-15SB-XBI		740.000
C40HH-20SB-XBI		890.000
C40HH-30SB-XBI		1.040.000

		C40HF-05PB-3		550.000
		C40HF-10PB-3		650.000
		C40HF-15PB-3		740.000
		C40HF-20PB-3		890.000
		C40HF-30PB-3		1.040.000
		C40HF-05PB-1A		550.000
		C40HF-10PB-1A		650.000
		C40HF-15PB-1A		740.000
		C40HF-20PB-1A		890.000
		C40HF-30PB-1A		1.040.000
XGT Panel (Touch Panel)				0
4.1 Inch		XP10BKA/DC	4.1" Mono green LCD(192×64Dot), DC24V power	3.950.000
		XP10BKB/DC	4.1" Mono green LCD(192×64Dot), DC24V power (built-in RTC)	6.140.000
4 Inch		eXP20-TTA/DC	4" TFT LCD, 65,536 Colors, DC24V power,based on Win CE core	5.120.000
5.7 Inch		XP30-BTE/DC	5.7" Mono blue LCD, 320x240pixels, 8 Gray, DC24V power, based on Win CE core (economical type)	9.010.000
		XP30-BTA/DC	5.7" Mono blue LCD, 320x240pixels, 8 Gray, DC24V power, based on Win CE core	13.590.000
		XP30-BTB/DC	5.7" Mono blue LCD, 320x240pixels, 8 Gray, DC24V power, based on Win CE professional plus	15.150.000
		XP30-TTA/DC	5.7" TFT LCD, 320x240pixels, 65,536 Colors, DC24V power, based on Win CE core	16.220.000
		XP30-TTB/DC	5.7" TFT LCD, 320x240pixels, 65,536 Colors, DC24V power, based on Win CE professional plus	21.290.000
		XP30-TTE/DC	5.7" TFT LCD, 320x240pixels, 256 Colors, DC24V power, based on Win CE	9.650.000
7 Inch		eXP40-TTE/DC	7" TFT LCD, 65,536 Colors, DC24V power,based on Win CE core	6.530.000
		eXP40-TTA/DC	7" TFT LCD, 65,536 Colors, DC24V power,based on Win CE core with Ethernet port	6.770.000
		XP40-TTE/DC	7" TFT LCD, 65,536 Colors, DC24V power,based on Win CE core	13.590.000
		XP40-TTA/DC	7" TFT LCD, 256 Colors, DC24V power, based on Win CE	15.150.000
8.4 Inch		XP50-TTA/DC	8.4" TFT LCD, 640x480pixels, 65,536 Colors, DC24V power,based on Win CE core	24.800.000
		XP50-TTB/DC	8.4" TFT LCD, 640x480pixels, 65,536 Colors, DC24V power, based on Win CE professional plus	24.800.000

		IXP50-TTA/DC	8.4" TFT 16,777,216 colors, SVGA(800×600 dots), DC12/24V power, based on Win CE core	24.800.000
10.2 Inch		eXP60-TTA/DC	10.2" TFT LCD, 65,536 Colors, DC24V power, based on Win CE core with Ethernet port	10.960.000
10.4 Inch		XP70-TTA/AC	10.4" TFT LCD, 640x480pixels, 65,536 Colors, AC100~240V power, based on Win CE core	33.130.000
		XP70-TTB/AC	10.4" TFT LCD, 640x480pixels, 65,536 Colors, AC100~240V power, based on Win CE professional plus	33.130.000
		XP70-TTA/DC	10.4" TFT LCD, 640x480pixels, 65,536 Colors, DC24V power, based on Win CE core	33.130.000
		IXP70-TTA/AC	10.4" TFT 16,777,216 colors, SVGA(800×600 dots), AC100~240V power, based on Win CE core	33.130.000
		IXP70-TTA/DC	10.4" TFT 16,777,216 colors, SVGA(800×600 dots), DC12/24V power, based on Win CE core	33.130.000
12.1 Inch		XP80-TTA/AC	12.1" TFT LCD, 800x600pixels, 65,536 Colors, AC100~240V power, based on Win CE core	37.510.000
		XP80-TTB/AC	12.1" TFT LCD, 800x600pixels, 65,536 Colors, AC100~240V power, based on Win CE professional plus	37.510.000
		XP80-TTA/DC	12.1" TFT LCD, 800x600pixels, 65,536 Colors, DC24V power, based on Win CE core	37.510.000
		IXP80-TTA/AC	12.1" TFT 16,777,216 colors, SVGA(800×600 dots), AC100~240V power, based on Win CE core	37.510.000
		IXP80-TTA/DC	12.1" TFT 16,777,216 colors, SVGA(800×600 dots), DC12/24V power, based on Win CE core	37.510.000
15 Inch		IXP90-TTA/AC	15" TFT 16,777,216 colors, XGA(1024×768 dots), AC100~240V power, based on Win CE core	45.410.000
		IXP90-TTA/DC	15" TFT 16,777,216 colors, XGA(1024×768 dots), DC12/24V power, based on Win CE core	45.410.000
Cable		XPO-USBC	USB TO USB CABLE	4.380.000
InfoU (SCADA S/W)				0
Developer & Runtime Version		InfoU-RC-75	HMI, InfoU-RC-75-Lite, EXP (MOQ: 5EA)	12.500.000
		InfoU-RC-150	150 tags	26.790.000
		InfoU-RC-500	500 tags	49.970.000
		InfoU-RC-1K	1,000 tags	60.680.000
		InfoU-RC-2K	2,000 tags	71.400.000
		InfoU-RC-MAX	Unlimited tags	99.930.000
Runtime Version		InfoU-RT-75	78 tags	12.500.000
		InfoU-RT-150	150 tags	21.380.000
		InfoU-RT-500	500 tags	35.680.000
		InfoU-RT-1K	1,000 tags	46.390.000

		InfoU-RT-2K	2,000 tags	57.110.000
		InfoU-RT-MAX	Unlimited tags	78.500.000
Web version		InfoU-OP-WEBMAX	InfoU-RC + Web server [Unlimited access]	331.950.000
		InfoU-OP-WEBMAX/150	unlimited client license + InfoU-RC-150	50.120.000
		InfoU-OP-WEBMAX/500	unlimited client license + InfoU-RC-500	93.550.000
		InfoU-OP-WEBMAX/1K	unlimited client license + InfoU-RC-1K	113.560.000
		InfoU-OP-WEBMAX/2K	unlimited client license + InfoU-RC-2K	133.620.000
Manual		MANUAL,ENGLISH,InfoU	InfoU English manual	1.680.000
Series	Part number		Description	
Motion controller		XMC-E32A	Stand alone motrion controller	25.520.000